



| | | | | |
|----------------------|----------------------|----------|---|-------------------------|
| Spec/Range | | | | |
| Computer Connections | | Direct | | 32 |
| | | Max | | 512 |
| Console Connections | | Local | | 1 |
| | | Remote | | 2 |
| Port Selection | | | | Pushbutton, OSD, Hotkey |
| Connectors | Console Ports | Keyboard | 1 x 6-pin Mini DIN Female (Purple) 1 x USB Type A Female (White) | |
| | | Video | 1 x HD-15 Female (Blue) | |
| | | Mouse | 1 x 6-pin Mini DIN Female (Green) 1 x USB Type A Female (White) | |
| | KVM Ports | | 32 x RJ-45 Female (Black) | |
| | Power | | 1 x 3-prong AC socket | |
| | LAN | | 2 x RJ-45 Female (Black) | |
| | PCI | | 1 x RJ-45 Female (Black) | |
| | Modem | | 1 x RJ-45 Female (Black) | |
| | USB | | 3 x USB Type A Female (White) | |
| Switches | Reset | | 1 x Semi-recessed Pushbutton | |
| | Power | | 1 x Slide | |
| | Port Selection | | 2 x Pushbutton | |
| LEDs | On Line | | 32 (Green) | |
| | Selected | | 32 (Orange) | |
| | Power | | 1 (Blue) | |
| | Link | | 1 (Green) | |
| | 10 / 100 / 1000 Mbps | | 1 (Red / Red + Green / Green) | |
| Emulation | Keyboard/Mouse | | USB, PS/2, Serial | |
| Video | | | 1600x1200 @ 60Hz | |
| Scan Interval | | | 1-255 Seconds | |
| IP Rating | | | 100-240VAC, 50/60Hz, 1.0A | |
| Power consumption | | | 110W / 33.40W; 230V / 33.60W | |
| Environment | Operating Temp. | | 0 - 50°C | |
| | Storage Temp. | | -20 - 60°C | |
| | Humidity | | 0 - 80% RH, Non-condensing | |

Physical Properties

Housing

Metal

Weight

5.59 kg

Dimensions
(L x W x H)

43.38 x 41.35 x 4.42 cm (19"150)